



# Glazed Ceramic Wall Tile

## LEVANTER

### Technical Specifications 4x16

Technical Characteristics	ASTM Test	Standard	Result
Water Absorption %	ASTM C373	>10% ; <17%	Pass
Caliber Range	ASTM C499	<ul style="list-style-type: none"><li>• Length 402 mm: <math>\pm 0.80</math> mm</li><li>• Width 100 mm: <math>\pm 0.25</math> mm</li></ul>	Pass
Dimensionality (Warpage Diagonal)	ASTM C485	Min -0.3 mm ; Max +0.4 mm	Pass
Dimensionality (Warpage Edge)	ASTM C485	<ul style="list-style-type: none"><li>• Length 402 mm: Min -1.00 mm; Max +1.30 mm</li><li>• Width 100 mm: Min -0.30 mm ; Max +0.40 mm</li></ul>	Pass
Wedging	ASTM C502	<ul style="list-style-type: none"><li>• Length 402 mm: <math>\pm 0.80</math> mm</li><li>• Width 200 mm: <math>\pm 0.5</math> mm</li></ul>	Pass
Crazing Resistance	ASTM C424	Conform	Pass
Surface Quality	EN ISO 10545-2	A minimum of 95 % of tiles examined (Total flooring), shall be without visible defects at 1 meter with daylight reflection.	Pass

#### Acacia Tile Inc.

5463 50th Ave • Delta, BC V4K2A1 • CA

604-757-0986

[info@acaciatile.com](mailto:info@acaciatile.com)